

JCB ROUGH TERRAIN FORK LIFT 926/930

OPERATING WEIGHTS:
LIFT CAPACITY:

5910 to 6340 kg (13029 to 13977lb)
2.6 to 3.0 tonnes (5732 to 6613 b)

DIMENSIONS	926	930
	m (ft-in)	m (ft-in)
Overall cab height	2.57 (8-5)	2.57 (8-5)
Overall width (over tyres)	2.20 (7-2½)	2.20 (7-2½)
Overall length to front carriage (industrial or bar)	3.60 (11-10)	3.60 (11-10)
Inside width of cab	1.16 (3-9½)	1.16 (3-9½)
Front track	1.80 (5-11)	1.80 (5-11)
Wheel base	2.13 (7-0)	2.13 (7-0)
Ground clearance	0.37 (1-2½)	0.37 (1-2½)
Mast closed height		
3.6m mast	2.95 (9-8)	2.95 (9-8)
4.5m mast	2.41 (7-10)	2.41 (7-10)
5.5m mast	2.95 (9-8)	2.95 (9-8)
6.55m mast	3.32 (10-11)	3.32 (10-11)
Mast open height		
3.6m mast	4.78 (15-8)	4.78 (15-8)
4.5m mast	5.41 (17-9)	5.41 (17-9)
5.5m mast	6.61 (21-8)	6.61 (21-8)
6.55m mast	7.67 (25-2)	7.67 (25-2)
Mast tilt forwards	18°	18°
Mast tilt backwards	10°	10°
Load centre	0.50 (1-8)	0.50 (1-8)
Free lift (4.5m mast only)	1.46 (4-9½)	1.46 (4-9½)

TURN RADIUS & GROUND LINE ANGLES

	m (ft-in)	m (ft-in)
Outside turn radius	4.49 (14-8¾)	4.49 (14-8¾)
Departure angle	53°	43°
Obstruction angle	51°	51°

WEIGHT

	kg (lb)	kg (lb)
Overall weight	5910 (13025)	6340 (13973)

The above data based on the following specification: Standard fork size 1067 x 100 x 50 mm (42 x 4 x 2 in)

TYRES

	926		930
Standard tyres	16.5/85-24		16.5/85-24
(UK) Front	Traction		Traction
Rear 2WD	12.5/80-18		12.5/80-18
	Rib and bar		Rib and bar
Rear 4WD	12.5/80-18	10.5-18	12.5/80-18
	Traction	Traction	Traction

SERVICE CAPACITIES

	litres (UK gal)
Fuel tank	88 (19.0)
Hydraulic tank	60 (13)
Coolant	17 (3.7)

OPTIONS

Auxiliary carriage services via hose reel for powered attachments. Wheel and tyres sets. Tinted cab glazing. Suspension seat. Seat belt. Roof screen wash/wipe. Flashing roof beacon. Fire extinguisher. Cab exterior mirrors. Front screen bars. Optional rear fenders. Reversing lights. Propshaft guards. Chaff guard. Air pre-cleaner. Engine fan guard kit. Hose guard kits. Load guard.